



D.O.P Certificate No:
WW 0001

Declaration of Performance

Window Widgets Ltd hereby declare:

Window Baypole Jacks, for Structural use in the Installation of Windows, Doors & Conservatories,

conform to the provisions of Annex ZA, BS EN 1090-1:2009+A1:2011
System 2+.

Initial inspection of manufacturing plant and Factory Production Control (FPC) and continuous surveillance, assessment and evaluation of the Factory Production Control is conducted by:

UKCA Notified Body:

BSI Group
Kitemark House
Maylands Avenue
Hemel Hempstead
HP2 4SQ

Certificate Number:

0086-CPR-638382

CE Notified Body:

BSI Group The Netherlands B.V.
Say Building
John M. Keynesplein 9
1066 EP
Amsterdam

Certificate Number:

2797-CPR-742039

Structural Characteristics

Load Bearing:	Refer to structural calculations, see BBA Report No. 2630
Design:	According to EN 1993-1
Manufacturing:	According to component specification and EN 1090-2 & EN 1090-3: Execution Class 2 (EXC2)
Resistance to Fire:	NPD
Fatigue Strength:	NPD

Manufacturing Characteristics

Tolerances on Dimensions:	As EN 1090-2 for steel components As EN 1090-3 for aluminium components
Weldability:	X5CrNi18-10 according to EN1088-3 S275 according to EN1025-2 EN AW-6063 T6 and EN AW-5083 according to EN1011-4 and EN1999-1-1
Fracture Toughness:	X5CrNi18-10 - 60 J @ 20°C S275 - 27 J @ 0°C Not required for aluminium components
Deformation at serviceability limit state:	See design brief and calculations in BBA Report No. 2630
Reaction to Fire:	Class A1
Release of Cadmium:	NPD
Emission of Radioactivity:	NPD
Durability:	Surface preparation as EN 1090-2 preparation grade P2

Manufactured by:



Window Widgets Ltd,
Unit C Quedgeley West
Business Park,
Bristol Road,
Gloucester,
GL2 4PA.

Tel: (01452) 300912
Fax: (01452) 416654
www.windowwidgets.co.uk

Signed for, and on behalf of the manufacturer, by:

Michael Hart (Technical Director)
March, 2025